



## **PREMIUM ACRYLIC BONDER**

### PRODUCT DESCRIPTION

**COMPLETE COATINGS** Premium Acrylic Bonder is specially formulated for use on cementitious substrates.

**COMPLETE COATINGS** Premium Acrylic Bonder is made from the highest quality raw materials to provide a long lasting adhesive base for stucco, acrylic latex and elastomeric wall coatings and underlayments.

This bonder will increase the adhesion of the topcoat by sealing the porous surface of stucco or other substrates enabling the coating to be spread farther. **COMPLETE COATINGS** Premium Acrylic Bonder will stop efflorescence from occurring and can seal a surface that is currently chalking.

- Alkali Resistant
- Easily Applied
- Excellent Dry Time
- Low Odor
- Excellent Adhesion
- Easy Cleanup

### **PHYSICAL PROPERTIES:**

|                                 |                                    |
|---------------------------------|------------------------------------|
| <b>Vehicle</b>                  | 100% Acrylic Resin                 |
| <b>Thinner / Reducer</b>        | Water                              |
| <b>Weight Solids</b>            | 35 +/- 2%                          |
| <b>Volume Solids</b>            | 25% +/- 2%                         |
| <b>Volatile Organic Solvent</b> | 150 grams/liter                    |
| <b>Weight / Gallon</b>          | 9.8 lbs. /gal.                     |
| <b>Standard Coverage</b>        | 150 - 250 ft <sup>2</sup> / gallon |
| <b>Viscosity (Kreb Units)</b>   | 80-85 K.U.                         |
|                                 |                                    |
|                                 |                                    |

### **USES:**

- Stucco
- Masonry
- Concrete Structures

Bonder1

The information contained in this document is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Complete Coatings knowledge or obtained from sources believed by Complete Coatings to be accurate. Complete Coatings does not assume any legal responsibility for use or reliance upon the information contained in this document. Tests should be carried out only by qualified professionals. Before using any chemical product, read its Material Safety Data Sheet.

# **PREMIUM ACRYLIC BONDER**

---

## **PRODUCT DESCRIPTION**

### **SHELF LIFE:**

Twenty-four months when stored at an ambient temperature of 75 degrees Fahrenheit at 0 - 90% humidity.  
DO NOT ALLOW TO FREEZE.

### **SURFACE PREPARATION:**

Surfaces should be free of defects and contamination. All contaminants such as dirt, oils, wax and medium to heavy chalk must be removed to ensure proper adhesion to the substrate. Cementitious surfaces should be cleaned and etched with a 10% muriatic acid solution, then thoroughly rinsed with water to remove any traces of acid. All cleaners or removers must be rinsed clean from the substrate. Chipping or peeling paint must be removed prior to application of bonder. Power wash or power brush severe substrate. Mildew must be killed and removed by using a commercial mildew remover or with a solution of 1 cup of household bleach with 3 cups of tap water. Do not add certain types of detergents and ammonia to the bleach / water solution. Rinse substrate thoroughly and allow to dry. Careful and extensive surface preparation is the key to a successful and long lasting job. Please get the most out of the products you buy.

### **APPLICATION:**

Brush, roll, or spray. Do not dilute. If the temperature is very high or very dry, moisten the substrate with water.

### **CLEAN-UP:**

Clean up overspray with a mild soap and water solution. On concrete surfaces use a mildly soap and water solution to scrub the surface, for heavier surfaces use a wire brush. Dispose of all waste in accordance with local state and federal organizations.

### **KEEP OUT OF THE REACH OF CHILDREN.**

**Do not take internally. Wash hands or any part of your body that comes into contact with this product. Avoid breathing vapor, mist or fumes from fires.**

**Do not use in tank or pit without proper protection. Use product in accordance with this product data sheet, any variance voids all warranties and liabilities.**

**Read Material Safety Data Sheet before use of this product.**

**COMPLETE COATINGS**  
A DIVISION OF INCIDE TECHNOLOGIES, INC  
50 NORTH FOURTY-FIRST AVENUE  
PHOENIX, ARIZONA 85009-4618  
(602) 233-2961 (800) 777-4569  
FAX (602) 272-4864

Bonder2

---

The information contained in this document is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Complete Coatings knowledge or obtained from sources believed by Complete Coatings to be accurate. Complete Coatings does not assume any legal responsibility for use or reliance upon the information contained in this document. Tests should be carried out only by qualified professionals. Before using any chemical product, read its Material Safety Data Sheet.