



ACRYLIC CLEAR SEALER



Vehicle:	100% Latex Acrylic Resin
Thinner / Reducer:	Water
Weight Solids:	33 +/- 2%
Volume Solids:	30 +/- 2%
Volatile Organic Solvent:	95.74
Weight / Gallon:	8.55 lbs/gal.
Standard Coverage:	150 to 200 sq ft/Gal Stucco Coverage:
Coverage on porous & rough stucco:	80 sq ft/Gal
Gloss @ 60 deg:	80-90
Viscosity Zahn #2:	34 Seconds.
Dry Time (77 F & 50% Rel. Humidity.)	
To Touch:	30 Minutes
To Recoat:	2 - 24 Hours

SHELF LIFE:

Twenty-four months when stored at an ambient temperature of 75 degrees Fahrenheit at 0 - 90% humidity.

DO NOT ALLOW TO FREEZE.

SURFACE PREPARATION:

Surfaces should be free of defects and contamination. All contaminants such as dirt, oils, wax and medium to heavy chalk must be removed to ensure proper adhesion to the substrate. All cleaners or removers must be rinsed clean from the substrate. Chipping or peeling paint must be removed prior to application of paint. Power wash or power brush severe substrates. Mildew must be killed and removed by using a commercial mildew remover or with a solution of 1 cup of household bleach with 3 cups of tap water. Do not add certain types of detergents and ammonia to the bleach / water solution. Rinse substrate thoroughly and allow drying. Applying sealants to all cracks and gaps is very important and will drastically affect how long the coating lasts. Water must be stopped from penetrating beneath the coating. The best and most appropriate sealant is an elastomeric caulk. With excellent adhesion and elongation characteristics this sealant will last a long time. Careful and extensive surface preparation is the key to a successful and long lasting job. Please get the most out of the products you buy.

APPLICATION:

DO NOT APPLY WHEN AMBIENT OR SURFACE TEMPERATURES ARE BELOW 50 DEGREES F OR ABOVE 100 DEGREES F. Do not apply in overly hot times of the day and try to avoid applying in direct sunlight. Brush, roll, or spray. If spraying porous or rough textured substrates, paint must be back rolled. **DO NOT** thin. Do not apply coating when weather conditions are dangerous to the coatings natural dry cycle. Do not apply to horizontal surfaces where standing water may accumulate. For optimum results spray coating with an industrial airless sprayer and back roll with a 1 1/4" roller, this will ensure penetration and film uniformity.

KEEP OUT OF THE REACH OF CHILDREN.

THIS PRODUCT CONTAINS NO LEAD OR MERCURY.

Do not take internally. Wash hands or any part of your body that comes into contact with this product. Avoid breathing vapor, mist or fumes from fires.

Do not use in tank or pit without proper protection. Use product in accordance with this product data sheet, any variance voids all warranties and liabilities.

Read Material Safety Data Sheet before using this product.