



Cool Feet
 PRODUCT DESCRIPTION



COMPLETE COATINGS Cool Feet is a High Quality Acrylic Ceramic Deck Coating manufactured for the exterior weathering of the Southwestern Environment. **COMPLETE COATINGS Cool Feet** is made for solar reflection, adhesion and exterior hold-up on new or refinished cementitious decks. This system is specially formulated to adhere to porous substrates with mild alkalinity. Best results are obtained if primed with **COMPLETE COATINGS Premium Primer and Sealer**. **COMPLETE COATINGS Cool Feet** can be tinted to a variety of stock colors as well as many custom colors.

- Excellent U.V. Resistance
- Easily Applied
- Excellent Color Recoatability
- Low Dirt Pick Up
- Stain Resistant
- Excellent Durability
- Excellent Weatherability
- Great Resistance to Early Chalking

PHYSICAL PROPERTIES:

Colors	White & Off-Whites
Vehicle	Acrylic Resins
Thinner / Reducer	Water
Weight Solids	68 +/- 2%
Volume Solids	54 +/- 2%
Volatile Organic Solvent	90 grams/liter
Weight / Gallon	10.0 lbs/gal. +/- .2lbs
Standard Coverage	100 ft ² / gallon @ 8 mils
Gloss @ 60 deg	10 max.
Viscosity (Kreb Units)	110 K.U.
Dry Time (77 F & 50% Rel. Humidity.)	To Touch: 4 Hours To Recoat: Overnight

* Standard Average taken over a series of tests and related physical properties.

SHELF LIFE:

This product will retain its usefulness if used before twenty-four months from the manufactured date, when stored at an ambient room temperature of 75 degrees Fahrenheit at 0 - 90% humidity.
 DO NOT ALLOW TO FREEZE.

Cool Feet

PRODUCT DESCRIPTION

SURFACE PREPARATION:

Surfaces should be free of defects and contamination. All contaminants such as dirt, oils, wax and medium to heavy chalk must be removed to ensure proper adhesion to the substrate. Solutions made with TSP and Clorox Bleach at weight measurements of 1:1 and added to 12 parts water will clean cement and similar surfaces adequately. Cleaners must be thoroughly rinsed clean from the substrate. Chipping or peeling paint must be removed prior to application of paint. Power wash or power brush severe substrates. Acid washes are not recommended. Mildew must be killed and removed by using a commercial mildew remover or a solution of 1 cup of household bleach with 3 cups of tap water. Rinse substrate thoroughly and allow to dry. High alkaline substrates can be neutralized by using dilute mixtures of 10% phosphoric acid and water and rinsed well. All acid residue must be removed. It is recommended that the pH is checked throughout the building structure to ensure adequate application conditions. All new cementitious substrates must be aged 28 days before application of primer.

APPLICATION:

Make sure that the substrate is neutralized before application of coatings. Brush, roll, or spray product. Thinning product is not recommended. When applying this product it is recommended that the film thickness is periodically checked to be sure of an accurate 8 mils per coat. To check coating thickness by application procedures; apply product to a 4' x 8' piece of plywood and check the film thickness per even coat applied. This will give the applicator an accurate indication of a uniform film. Do not apply coating if weather conditions might yield rain, snow, or other extreme weather conditions. A topcoat of Complete Coatings clear acrylic sealer is recommended if heavy outdoor furniture is placed on the deck surfaces.

CLEAN-UP:

Clean brushes, roller covers and spray rig with ordinary tap water. Clean up overspray with a mild soap and water solution. On concrete use a soap and water solution and a wire brush to remove most of the paint from the substrate. Dispose of all waste in accordance with local state and federal organizations.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally. Wash hands or any part of your body which comes into contact with this product. Avoid breathing vapor, mist or fumes from fires.

Do not use in tank or pit without proper protection. Use product in accordance with this product data sheet, any variance voids all warranties and liabilities.

Read Material Safety Data Sheet before use of this product.

COMPLETE COATINGS
A DIVISION OF INCIDE TECHNOLOGIES, INC.
50 NORTH FOURTY-FIRST AVENUE
PHOENIX, ARIZONA 85009-4618
(602) 233-2961 (800) 777-4569
FAX (602) 272-4864

Cool Feet 2

The information contained in this document is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Complete Coatings knowledge or obtained from sources believed by Complete Coatings to be accurate. Complete Coatings does not assume any legal responsibility for use or reliance upon the information contained in this document. Tests should be carried out only by qualified professionals. Before using any chemical product, read its Material Safety Data Sheet.