



## **SELECT FLEX™ Textured Elastomeric Caulk**

---

**COMPLETE COATINGS** uses advanced polymer technology along with the highest quality materials to create this flexible, long-lasting caulk that adds value and durability to any project. Easily applied, SELECT FLEX™ CAULK requires minimal maintenance. The flexibility and crack filling properties of SELECT FLEX™ CAULK insure homeowners' and commercial property owners' satisfaction well into the future. SELECT FLEX™ CAULK provides the value-added solution for exterior and interior applications. Fast application time and excellent performance make for an economical advantage from start to finish.

COMPLETE COATINGS SELECT FLEX™ CAULK will fill cracks on the exterior of stucco and adobe finished homes with minimal shrinkage and wrinkling. COMPLETE COATINGS SELECT FLEX™ CAULK will maintain its elasticity even in colder temperatures.

- Excellent Durability
- Textured
- Mildew Resistant
- Paintable
- Custom Colors Available
- Excellent Ultra Violet Resistance

### **SPECIFICATIONS**

TEST	METHOD	RESULTS
Flexibility	ASTM D-522	Pass
Surface Burning	ASTM E-84	Class A (15 Flame Spread, 25 Smoke)
Adhesion	ASTM C-297	> 95 to Concrete
Mildew Resistance	ASTM D-3273	No Growth
Freeze-Thaw Resistance	ASTM D-2243	Pass
Wind Driven Rain Resistance	TT-C-555B (a)	Pass – No Penetration
Water Absorption .2 lbs. max.		0.06 pounds
Vehicle Type		Acrylic Elastomeric Polymer
Weatherability – 2000 Hours	ASTM G-53	No Cracking
Low Temperature Cracking	ASTM D-522	None – Flexibility Maintained
Tensile Strength	ASTM D-412	115 psi
Dirt Pickup Resistance	Lab Method	89% Reflectance Retained
Elongation	ASTM D-412	200%
Flexibility	ASTM D-522	Pass
Water Vapor Permeability	ASTM D-1653	>34 U.S. Perms
Peel Adhesion	ASTM C-794	Pass
Dry		20 lbs. per linear inch
Wet		5 lbs. per linear inch
Approximate Coverage		51 linear feet per cartridge for a 1/8" x 1/4" bead

---

The information contained in this document is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Complete Coatings knowledge or obtained from sources believed by Complete Coatings to be accurate. Complete Coatings does not assume any legal responsibility for use or reliance upon the information contained in this document. Tests should be carried out only by qualified professionals. Before using any chemical product, read its Material Safety Data Sheet.

# **SELECT FLEX™ Textured Elastomeric Caulk**

---

## **SHELF LIFE:**

Twenty four months when stored at an ambient temperature of 75 degrees Fahrenheit at 0 - 90% humidity.  
DO NOT ALLOW TO FREEZE.

## **SURFACE PREPARATION:**

All cementitious surfaces should be below a pH of 10 and primed using **COMPLETE COATINGS** Premium Primer and Sealer following the manufacturer's directions. Surfaces should be free of defects and contamination. All contaminants such as dirt, oils, wax and medium to heavy chalk must be removed to ensure proper adhesion to the substrate. All cleaners or removers must be rinsed clean from the substrate. Chipping or peeling paint must be removed prior to application of primer. Power wash or power brush severe substrate Mildew must be killed and removed by using a commercial mildew remover or with a solution of 1 cup of household bleach with 3 cups of tap water. Do not add certain types of detergents and ammonia to the bleach / water solution. Rinse substrate thoroughly and allow to dry. **Apply all caulk after the stucco is properly primed for the best performance.** Seal around all openings and penetrations. This includes windows, doors and wood trim. Other areas are dryer vents, any plumbing penetrations and at the wall to the soffit. Careful and extensive surface preparation is the key to a successful and long lasting job. Please get the most out of the products you buy.

## **APPLICATION:**

Do not apply on exterior surfaces when rain is expected. Apply with a standard caulking gun. Cut nozzle at a 45° angle to desired thickness of bead. Use steady pressure to fill joints completely. For a neat appearance, smooth bead with a moistened cloth, float, brush or finger. Remove excess material with a moistened cloth before the surface skins over. For a straight edge, mask both sides of the joint with masking tape. For best results, cured beads should be between 1/8" – 1/2" wide and 1/8" – 1/2" deep. A 1/8" x 1/4" bead will yield approximately 51 linear feet of sealant per cartridge. **IMPORTANT:** Use backer rods or fiberglass tape for cracks and seams deeper than 1/4". Allow sealant to cure for at least 21 days before assessing overall sealant performance.

## **CLEAN-UP:**

Clean up tools and hands with a mild soap and water solution immediately after use and before compound dries. On concrete use the soap solution and a wire brush. Dispose of all waste in accordance with local state and federal organizations.

## **KEEP OUT OF THE REACH OF CHILDREN.**

**Do not take internally. Wash hands or any part of your body which comes into contact with this product. Avoid breathing vapor, mist or fumes from fires.**

**Do not use in tank or pit without proper protection. Use product in accordance with this product data sheet, any variance voids all warranties and liabilities.**

**Read Material Safety Data Sheet before use of this product.**

COMPLETE COATINGS  
A DIVISION OF INCIDE TECHNOLOGIES  
50 NORTH FOURTY-FIRST AVENUE  
PHOENIX, ARIZONA 85009-4618  
(602) 233-2961 (800) 777-4569  
FAX (602) 272-4864