



SURECURE PLUS™

PRODUCT DESCRIPTION

COMPLETE COATINGS SureCure Plus™ is specially formulated for use on and with cementitious substrates. It is packaged in a concentrated form and can be diluted with clean water to perform several functions. **COMPLETE COATINGS** SureCure Plus™ is made from the highest quality raw materials to provide a long lasting adhesive base for stucco, acrylic latex and elastomeric wall coatings and underlayments. SureCure Plus™ may be used as a cement modifier to increase the polymer content of bagged cement products while mixing them. SureCure Plus™ may also be used as a clear sealer over cementitious substrates.

When used as a bonder SureCure Plus™ will increase the adhesion of the topcoat by sealing the porous surface of stucco or other substrates enabling the coating to be spread farther. The Bonder will stop efflorescence from occurring and can seal a surface that is currently chalking. When used as a cement modifier, SureCure Plus™ functions as a glue to increase psi values as well as reducing the porosity of the cured concrete substrate. SureCure Plus forms an excellent durable, colorless film when used as a sealer. SureCure Plus™ is formulated to be diluted with clean water from a 1:1 to 2:1 ratio depending upon the use.

- Alkali Resistant
- Easily Applied
- Excellent Dry Time
- Low Odor
- Excellent Adhesion
- Easy Cleanup

PHYSICAL PROPERTIES:

Vehicle	100% Acrylic Resin
Thinner / Reducer	Water
Weight Solids	48 +/- 2%
Volume Solids	30% +/- 2%
Volatile Organic Solvent	150 grams/liter
Weight / Gallon	9.8 lbs. /gal.
Standard Coverage	150 - 250 ft ² / gallon
Viscosity (Kreb Units)	80-85 K.U.

USES:

- Stucco
- Masonry
- Concrete Structures

The information contained in this document is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Complete Coatings knowledge or obtained from sources believed by Complete Coatings to be accurate. Complete Coatings does not assume any legal responsibility for use or reliance upon the information contained in this document. Tests should be carried out only by qualified professionals. Before using any chemical product, read its Material Safety Data Sheet.

SURECURE PLUS™

PRODUCT DESCRIPTION

SHELF LIFE:

Twenty-four months when stored at an ambient temperature of 75 degrees Fahrenheit at 0 - 90% humidity.
DO NOT ALLOW TO FREEZE.

SURFACE PREPARATION:

Surfaces should be free of defects and contamination. All contaminants such as dirt, oils, wax and medium to heavy chalk must be removed to ensure proper adhesion to the substrate. Cementitious surfaces should be cleaned and etched with a 10% muriatic acid solution, then thoroughly rinsed with water to remove any traces of acid. All cleaners or removers must be rinsed clean from the substrate. Chipping or peeling paint must be removed prior to application of bonder. Power wash or power brush severe substrate. Mildew must be killed and removed by using a commercial mildew remover or with a solution of 1 cup of household bleach with 3 cups of tap water. Do not add certain types of detergents and ammonia to the bleach / water solution. Rinse substrate thoroughly and allow to dry. Careful and extensive surface preparation is the key to a successful and long lasting job. Please get the most out of the products you buy.

APPLICATION:

Brush, roll, or spray. Dilute according to use. If the temperature is very high or very dry, moisten the substrate with water.

CLEAN-UP:

Clean up overspray with a mild soap and water solution. On concrete surfaces use a mildly soap and water solution to scrub the surface, for heavier surfaces use a wire brush. Dispose of all waste in accordance with local state and federal organizations.

KEEP OUT OF THE REACH OF CHILDREN.

Do not take internally. Wash hands or any part of your body that comes into contact with this product. Avoid breathing vapor, mist or fumes from fires.

Do not use in tank or pit without proper protection. Use product in accordance with this product data sheet, any variance voids all warranties and liabilities.

Read Material Safety Data Sheet before use of this product.

COMPLETE COATINGS
A DIVISION OF INCIDE TECHNOLOGIES
50 NORTH FOURTY-FIRST AVENUE
PHOENIX, ARIZONA 85009-4618
(602) 233-2961 (800) 777-4569
FAX (602) 272-4864

The information contained in this document is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Complete Coatings knowledge or obtained from sources believed by Complete Coatings to be accurate. Complete Coatings does not assume any legal responsibility for use or reliance upon the information contained in this document. Tests should be carried out only by qualified professionals. Before using any chemical product, read its Material Safety Data Sheet.